

ACE2 NEW GENERATION

THE KING OF THE MEDIUM RANGE



INFORMATION

ACE2 NEW GENERATION is suitable for controlling several types of motors (AC induction, SPM, IPM, SRM, SRPM), in the range from 4 kW to 12 kW continuous power, adopted in battery-powered electric and hybrid vehicles. Speed or torque control are available. The I/Os accommodate a wide range of vehicle controls and sensors. ACE2 NEW GEN can also interface with a wide range of external devices via CAN bus.

APPLICATIONS



Tow tractors and airport ground support vehicles



Material handling and AGV



Aerial-access equipment (AWP)



Construction equipment




E-mobility




Agriculture

DIMENSIONS


mm [in]




Base plate



Longitudinal heatsink



Transversal heatsink



Liquid cooled

Available with or without power fuse.

ACE2

NEW GENERATION

THE KING OF THE MEDIUM RANGE

FEATURES

Description	Standard	Premium
Connector	23 pins Ampseal	35 pins Ampseal
Digital inputs, active high	3	8
Digital inputs, active low	2	3
Analog inputs	2	4
ON/OFF outputs	-	1
PWM voltage-controlled outputs	2	4
PWM current-controlled output	-	1
CAN bus interface	1	1
Input for motor thermal sensor	1	1
Encoder interface	1	1
3-Hall interface	-	1
Auxiliary supply output (+12/+5V)	2 (max 200 mA each)	
Sin-cos/Resolver interface	-	1 on demand
Microcontrollers	2	
Ambient temperature, operating	-40 °C ÷ +40 °C	(-40 °F ÷ 104 °F)
Ambient temperature, storage	-40 °C ÷ +85 °C	(-40 °F ÷ 185 °F)

Speed/position sensor interfaces different from single incremental encoder reduce the number of available digital/analog inputs.

MODEL CHART

Nominal DC voltage	DC Voltage range	Maximum AC current [Arms] ¹⁾	S2 60min AC current rating [Arms] ²⁾
24 V	10 V ÷ 35 V	350, 400, 450, 500, 550	175, 200, 225, 250, 275
36/48 V	10 V ÷ 62 V	350, 400, 450, 500, 550	175, 200, 225, 250, 275
72/80 V	30 V ÷ 115 V	250, 300, 350, 400	115, 150, 175, 180
96 V	30 V ÷ 130 V	250, 300, 350, 400	115, 150, 175, 180

Current ratings are based on an initial heat sink temperature of 40 °C (104 °F) and a maximum heat sink temperature of 85 °C (185 °F)

1) No airflow through the heat sink. 2) 100 m³/h airflow through the heat sink.

REGULATIONS

UL certificate	UL 583 compliant (AU3503)
EMC	EN 12895:2015+A1:2019
Functional safety	Designed to achieve EN1175 - 2020 requirements. Designed to achieve CATEGORY 2 according to EN13849; CATEGORY 3 achievable. Designed to achieve requirements of EN280
IP code	IP65